

Технические характеристики

	Условное обозначение	DN, мм	l ₀ ±15, мм	Типы наконечников, рис.1			Угол взаимного расположения наконечников, ± 5°, рис 3	Присоеди- тельная резьба, d	Наличие защиты, рис.2	
				Н	К	Г			П	М
P50.000	P50/08x460-КТ	8	460	-	+	+	0	M16x1,5-7H	-	-
-01	P50/08x460-КТ-М								-	+
-02	P50/08x460-КТ-П-М								+	+
-03	P50/08x560-КТ		560	-	+	+	0		-	-
-04	P50/08x560-КТ-М								-	+
-05	P50/08x560-КТ-П-М								+	+
-06	P50/08x520-НК		520	+	+	-	0		-	-
-07	P50/08x520-НК-М								-	+
-08	P50/08x520-НК-П-М								+	+
-09	P50/08x660-НН		660	+	-	-	0		-	-
-10	P50/08x660-НН-М								-	+
-11	P50/08x660-НН-П-М								+	+
-12	P50/08x1100-ГГ-П	1100	-	-	+	0	+	-		
-20	P50/16x450-КТ	16	450	-	+	+	0	M26x1,5-7H	-	-
-21	P50/16x450-КТ-М								-	+
-22	P50/16x450-КТ-П-М								+	+
-23	P50/16x500-КТ		500	-	+	+	0		-	-
-24	P50/16x500-КТ-М								-	+
-25	P50/16x500-КТ-П-М								+	+
-26	P50/16x660-КТ		660	-	+	+	0		-	-
-27	P50/16x660-КТ-М								-	+
-28	P50/16x660-КТ-П-М								+	+
-29	P50/16x720-ГГ75		720	-	-	+	75		-	-
-30	P50/16x720-ГГ75-М								-	+
-31	P50/16x720-ГГ75-П-М								+	+
-32	P50/16x720-ГГ135		720	-	-	+	135		-	-
-33	P50/16x720-ГГ135-М								-	+
-34	P50/16x720-ГГ135-П-М								+	+
-35	P50/16x720-ГГ180		720	-	-	+	180		-	-
-36	P50/16x720-ГГ180-М								-	+
-37	P50/16x720-ГГ180-П-М								+	+
-38	P50/16x650-НН		650	+	-	-	0		-	-
-39	P50/16x650-НН-М								-	+
-40	P50/16x650-НН-П-М	+						+		
-45	P50/16x410-КТ60-П-М	410	-	+	+	60	-	-		
-46	P50/16x410-КТ300-П-М						+	+		
-47	P50/16x450-КТ300-П-М					450	-	+	+	300
-50	P50/25x1150-НН	25	1150	+	-	-	0	M36x2-7H	-	-
-51	P50/25x1150-НН-М								-	+
-52	P50/25x1150-НН-П								+	-
-53	P50/25x1400-НГ		1400	+	-	+	0		-	-
-54	P50/25x1400-НГ-М								-	+
-55	P50/25x1400-НГ-П								+	-
-56	P50/25x1400-ГГ								-	+
-57	P50/25x1400-ГГ-М								-	+
-58	P50/25x1400-ГГ-П	+	-							